


Distribution trolley with antileackage



Satellite MDR



Satellite SI15-100



Easymousse



Satellite SI 40



Application

- Foaming
- Washing
- Spraying

Descriptive

304 L stainless steel trolley with antileakage area, equipped with a venturi system low or high pressure satellite


Performance

Easy-to-use:

- Compact in size
- Easy functioning
- Precision and adjustment dosing easy to do

Robustness:

- Stainless steel casing



Distribution trolley with antileackage

Technical characteristics

Satellite		SI 40 medium pressure			MDR Low pressure	Easymousse
Model	SINGLE dosing 1 product	DOUBLE dosing A choice of 2 products	DOUBLE venturi A choice of 2 products or simultaneously	DOUBLE dosing A choice of 2 products or simultaneously	Single dosing 1 product	
Material	304 L stainless steel			304 L stainless steel	304 L stainless steel	
Dimensions	Width: 720 mm Height: 780 mm Depth: 1050 mm			Width: 720 mm Height: 780 mm Depth: 1050 mm	Width: 720 mm Height: 780 mm Depth: 1050 mm	
Treatment	Chemically treated			Chemically treated	Chemically treated	
Fixed wheels Directional wheels	2 x 200 mm Ø 2 x 100 mm Ø			2 x 200 mm Ø 2 x 100 mm Ø	2 x 200 mm Ø 2 x 100 mm Ø	
Weight	45 kg			45 kg	45 kg	
Connections Water inlet Air inlet	1/2" male 8 ø			3/4" female 6 ø	3/8" female 8 ø	
Supply and pressure	Water: 15 to 64 bar Air: 6 bar min.			Water: 2 to 8 bar Air: 6 bar min.	Water: 15 to 64 bar Air: 6 bar min. High pressure upon request	
Dosing	1 to 10%			1 to 10%	1 to 10%	
Included accessories	-			20 m projection pipe Washing hose Foaming hose Spraying hose 5 m water supply kit	-	
COMMON EQUIPMENT						
<ul style="list-style-type: none"> > Space planned for 2 cans of 30 litres with antileackage area > Air pressure regulator and pressure gauge > Washing/dosing selection valve > Air selection valve > Foam quality adjustment thanks to air pressure reducer > Non return valve 						

All our materials are tested at the factory and supplied with instructions for use.